SMALL IN STATURE, BIG ON RESULTS

Boasting the latest printing technology, smart features and a compact footprint, the imageRUNNER ADVANCE C3500i III Series is ideally suited to mid-sized offices.

Canon imageRUNNER ADVANCE C3500i III Series

- Compact A3 Colour multifunction device
- Prints up to 30 ppm in colour
- Vivid & Vibrant V2 Colour
- Built in WiFi

Manage your projects with ease thanks to an intuitive design and advanced printing capabilities

- A3 mid-to-low-volume colour device with two speeds
- 10.1 inch full colour WVGA LCD display (touchscreen) with recently updated user interface
- Vivid and vibrant colour delivers a crisp, even finish
- Space-saving Inner Finisher incorporates ECO-Staple, Staple, and Staple-On-Demand functionalities
- My ADVANCE functions allow users to create their own personalised experience, tailored to meet their unique needs



Seamlessly integrate with key line-of-business systems

- Seamlessly integrate with key line-ofbusiness systems to power your digital transformation journey
- Collaborate with key line of business applications and external systems
- Personalised workflows give users the ability to take control of the way they want to manage their information so that it works best for them
- Leverage Canon's Multifunctional Embedded Application Platform (MEAP) to optimise processes with a range of powerful document, capture and output management solutions
- Supports integration with popular cloud services like Google Drive and Box*



Canon

Workers and contractors can achieve ultimate freedom and flexibility with Expanded Mobile OS Support

Mobile workflows are set up with built in WiFi and mobile applications to easily allow users to connect, print, scan and capture using Canon PRINT Business

ADVANC C35301

3

4

Canon

- Full support for Apple Airprint and Android Mopria Mobile Printing
- Simple and easy mobile connectivity with standard in-built WiFi



Streamline workflows while managing costs

- Forced Job Hold reduces paper and toner wastage
- Ability to change print settings at the device allows for extra control over jobs
- Blank page removal comes standard
 and works to reduce paper wastage



Safeguard data and ensure sensitive information remains secure

- Standard HDD Encryption works to prevent data leaks and keep confidential information protected
- Security settings have been consolidated to reduce administration
- Security policy support is also available



Designed to help achieve environmental goals

- Motion sensors and sleep recovery triggers work to reduce unnecessary power consumption
- Bio-based plastics are used throughout the machine for an environmentally friendly approach to printing performance

CONFIGURATION



Booklet Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 50 sheets (80 gsm)
- Supports optional internal 2/3 and 2/4 hole inner punchers



Staple Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 50 sheets (80 gsm)
- Supports optional internal and 4 hole inner punchers



imageRUNNER ADVANCE C3500i III SPECIFICATIONS



Type	A3 Colour Laser Multifunctional
Core Function Processor	Print, Copy, Scan, Send, Store and Optional Fax
Control Panel	Canon Dual Custom Processor (Shared) 10.1 inch TFT LCD WSVGA Colour Touchpanel
Memory	Standard: 3.0GB RAM
Hard Disk Drive	Standard: 250GB Maximum: 1TB
Mirroring Hard Disk Drive	Optional ITB
Interface Connection	Network: Standard: 1000Base-T/100Base-TX/10Base-TX/10Base-TX (IEEE 802.11 b/g/n), Optional: NFC, Bluetooth Low Energy Others: Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device), Optional: Serial Interface, Copy Control Interface
Paper Supply Capacity (A4, 80 gsm)	Standard: 1,200 sheets 2 x 550-sheet cassettes, 100-sheet multi-purpose tray Maximum: 2,300 sheets (with Cassette Feeding Unit-AP1)
Paper Sources (A4, 80gsm)	Standard: Two 550-sheet Paper Cassettes, 100-sheet Multi-purpose Tray Optional: Dual 550-sheet Paper Cassettes (Cassette Feeding Unit-AP1) Maximum: 2,300 Sheets
Paper Output Capacity (A4, 80gsm)	Standard: 250 Sheets Maximum: 3,450 Sheets (with Staple Finisher-AA1 or Booklet Finisher-AA1 and Copy Tray-J2
Finishing Capabilities	Standard: Collate, Group With Inner Finisher: Collate, Group, Offset, Staple, Eco-Staple, Staple On Demand With External Finisher: Collate, Group, Offset, Staple, Booklet ^T I, Hole Punch ^T 2, Eco-Staple, Staple On Demand ^{*1} Requires 203 Hole Puncher Unit-A1 or /4 Hole Puncher Unit-A1
Supported Media Types	Paper Cassettes 1/2: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Bond paper, Envelope Multi-purpose tray: Thin, Plain, Recycled, Thick, Colour, Transparency, Label, Tracing*, Envelope, Coated, Bond, Pre-punched * Some types of tracing paper cannot be used.
Supported Media Sizes	Paper Cassette 1: Standard size: A4, A5, A5R, A6R, B5, Envelopes: ISO-C5 ,Custom Size: 139.7 x 182.0 mm to 297.0 x 215.9 mm
	Paper Cassette 2: Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Envelopes: No.10 (COM10), Monarch, DL, Custom Size: 139.7 x 182.0 mm to 304.8 x 457.2 mm
	Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Envelopes: No.10 (COMI0), Monarch, ISO-C5, D1 Custom / Free size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm
Supported Media Weights	Cassette 1, 2: 52 to 220 gsm Cassette Feeding Unit: 52 to 220 gsm Multi-purpose tray: 52 to 300 gsm' * Thick (257 to 300 gsm): Standard format paper size (excl. SRA3), and Custom size/Free size (98.4 x 139.7mm to 304.8 x 457.2 mm) are supported. Coated is supported from 106 to 256 gsm. Duplex: 52 to 220 gsm
Warm-up Time	From Power On: 10 Seconds or Less* "Time from device power-on, until copy ready (not print reservation) From Deep Sleep Mode: 10 Seconds or Less Quick Startup Mode: 4 Seconds or Less*
Dimensions (W x D x H)	*Time from device power-on, until key operations can be performed on the touch panel display Standard with platen cover: 565 x 707 x 777 mm With Single Pass DADF-B1: 565 x 742 x 900 mm
Installation Space (W x D)	With DADF-AVI: 565 x 736 x 880 mm Basic : 978 x 1,123 mm (with Single Pass DADF- B1 + right cover open + Multi-purpose tray extension extended + paper cassette open) 978 x 1,117 mm (with DADF-AVI + right cover open + Multi-purpose t extension extended + Paper cassette open) Fully Configured : 1,620 x 1,123 mm (with Single Pass DADF- B1 + Booklet Finisher-AAI/Staple Finisher-AAI + right cover open + Multi-purpose tray extension extended + paper cassette open) 1,620 x 1,117 mm (with DADF-AVI + Booklet Finisher-AAI/Staple Finisher-AAI + right cover open + Multi-purpose tray extension extended + paper cassette open)
Weight*	Approx. 69 kg (with Platen Cover Type W) Approx. 81 kg (with Single Pass DADF-B1) Approx. 75 kg (with DADF-AV1) "including toner
Print Specifications	
Printing Method	Colour laser beam printing
Print Speed* (ppm, BW and CL) *(simplex)	iR-ADV C3530i III:Up to 30 (A4 / A5 / A5R / A6R), Up to 15 (A3), Up to 20 (A4R) iR-ADV C3520i III: Up to 20 (A4 / A4R / A5 / A5R / A6R), Up to 15 (A3)
Print Resolution (dpi)	600 × 600°, 1200 ×1200° *Laser Resolution
Page Description Languages	Standard: UFR II, PCL6, Adobe PS 3 (Option)
Direct Print	Direct printing available from USB memory, Advanced box, Remote UI and Web Access (Only PDF print from websites is supported.) Supported File Types: PDF, TIFF, JPEG, EPS, XPS
Printing from Mobile and Cloud	A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices. Please contact your sales representative for further information.
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese) , Barcode fonts*2 PS fonts: 136 Roman *1 Requires optional PCL International Font Set-A1 *2 Requires optional Barcode Printing Kit-D1
Print Features	Suspend Job Timeout, Profile Settings, Secured Print, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold printing
Operating System	UFR II: Windows 7 / 8.1/10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.9 or later) PCL: Windows 7 / 8.1/10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2012 R2 / Server 2016 RAC OS X (10.9 or later) PS: Windows 7 / 8.1/10 / Server 2008 / Server 2008 R2 / Server 2012 R2 / Server 2016, MAC OS X (10.9 or later)

Copy Speed* (ppm, BW and CL)	iR-ADV C3530i III: Up to 30 (A4/A5/A5R/A6R), Up to 15 (A3), Up to 20 (A4R) iR-ADV C3520i III: Up to 20 (A4/A4R/A5/A5R/A6R), Up to 15 (A3)
First-Copy-Out Time (A4 ; BW/CL)	Approx. 5.9/8.2 seconds or less
Copy Resolution (dpi)	600 × 600
Multiple Copies	Up to 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification Preset Reductions	25% - 400% (1% Increments) 25%, 50%, 61%, 70%, 81%, 86%
Preset Enlargements	115%, 122%, 141%, 200%, 400%
Basic Copy Features	Preset R/E Ratios by Area, Paper Setting, Previous Settings, Favourite Settings, Finishing, Two-Sided, Density Adjustment,
Special Copy Features	Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Pag Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Job Done Notice, Mirror Image, Cop ID Card,Skip Blank Pages, Detect Feeder Mult Sheet Feed, Free Size Original*, Adjust One-Touch Colour, Colour Balance, Area Designation
Scan Specifications	*Available with DADF-B1
Туре	Standard: Colour Flatbed Scan Unit Optional: Platen cover, Single-pass Duplexing Automatic Documen Feeder* (DADF-8I) or Duplexing Automatic Document Feeder (DADF-NI) [2-sided to 2-sided (Automatic with DADF)] * Detect Feeder Multi Sheet Feed is supported.
Document Feeder Paper Capacity	SINGLE PASS DADF-B1: 150 Sheets DADF-AV1: 100 Sheets
Supported media sizes	Platen: Supported Media Sizes description to : Platen: max. scanning size: 297.0 x 431.8 mm Document Feeder media size: SINGLE PASS DADF- B1 A3, A4, A4R, A5, A5R, B4, B5, B5R, B6R, Custom size: 128.0 x 139.7 mm to 304.8 x 431.8 mm DADF-AVI: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6, Custom size: 139.7 128.0 mm to 297.0 x 431.8 mm
Document Feeder Supported Media Weights	Single-sided scanning: 38 to 157 gsm (BW) Single-sided scanning: 64 to 157 gsm (CL) Double-sided scanning: 50 to 157 gsm (BW) Double-sided scanning: 64 to 157 gsm (CL)
Pull Scan Spec	Color Network ScanGear2. For both Twain and WIA Supported OS: Windows 7/8/8.1/10, Windows Server 2008/ Server 2008 R2/Server 2012/Server 2012 R2
Scan Resolution (dpi)	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100
Platen Acceptable Originals	Platen: Sheet, Book, 3-Dimensional Objects (Height: Up to 50 mm, Weight: up to 2kg) Paper Size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6
Scan Method	Send functionality available on all models Scan to USB Memory: Available on all models Scan to Mobile Devices and cloud-based services: A range of solution is available to provide scanning to mobile devices or cloud-based services depending on your requirements. Please contact your sales representative for further information. TWAINWIA Pull scanning available on all models
Scan Speed (ipm: BW and CL, A4)	SINGLE PASS DADF-B1 : 1-sided Scanning: 80 (300dpi), 51 (600 dpi) 2-sided Scanning: 160 (300dpi), 51 (600 dpi) DADF-AV1 : 1-sided Scanning: 70 (300dpi), 51 (600 dpi)
Canad Canadifications	2-sided Scanning: 35 (300dpi), 25.5 (600 dpi)
Send Specifications Optional/Standard	Standard on all models
Destination	E-mail/InternetFax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)
Colour Mode	Automatic-Colour Select (Full Colour/Grayscale), Automatic-Colour Select (Full Colour/Black-and-White), Full Colour, Grayscale, and Black-and-White
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send Resolution (dpi)	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100
Communication Protocol	File: FTP (TCP/IP), SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3
File Format	Standard: TIFF, JPEG, PDF(Compact, Apply policy, Optimize for Web, PDF A/t-b, Encrypted, Device Signature), XPS (Compact, Device Signature) Optional: PDF(Searchable, Trace&Smooth, User Singnature), XPS(Searchable, User Signature), Office Open XML PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages, Detect Feeder Multi Sheet Feed* *Available with DADF-B1
Fax Specifications	
Optional/Standard Maximum Number of	Optional on all models 2
Connection Lines Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution	A3, A4, A4R, A5*1, A5R*1, B4, B5*2, B5R*1 *1 Sent as A4
Sending/Recording Size	*2 Sent as B4 A5* and A5R* to A3 (*Sent as A4)
Fax Memory	Up to 30,000 pages
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes
Fax Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density (for Scanning), Sharpness, Copy Ratio Erase Frame, Job Build, Sender's Name (TT), Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Repor Detect Feeder Multi Sheet Feed' "Available with DADF-B1

Store Specifications Mail Box (Number Supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes,
Advanced Box	30,000 Maximum Pages Stored Communication Protocol: SMB or WebDAV
	Supported Client PC: Windows (Windows 7/8.1/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)
Advanced Box Available Disc Space	Approx. 16GB (Standard HDD) Approx. 480GB (with option ITB HDD)
Advanced Box Features	Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support
Memory Media	Standard: USB Memory
Security Specifications	
Security	Safeguard data and ensure sensitive information remains secure Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers. Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering. Security policy settings can be controlled with a dedicated password, configured from a central location, and exported Standard HDD Encryption works to prevent data leaks and keep confidential information protected
Authentication	Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in, unIFLOW Online Express Optional: unIFLOW, unIFLOW Online
Data	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated) Optional: Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)
Network	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME
Document	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan lock
Environmental Specifications Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity)
Power Requirements	220-240V(±10 %), 50/60Hz (±2 Hz), 4.0Amp
Power Consumption	Maximum: 1,500 W Standby: Approx. 38.8 W*1
	Sleep mode: Approx. 0.8 W *2 *1 Reference Value: measured one unit *2 0.8W sleep mode is not available in all circumstances due to certain settings.
Standards	ENERGY STAR® Qualified, Rated EPEAT (Gold), Blue Angel
Consumables	
Toner	NPG-67 TONER BK/C/M/Y
Toner Yield (Estimated @5% Coverage)	NPG-67 TONER BK: 36,000 pages NPG-67 TONER C/M/Y: 19,000 pages
Software and Printer Managen	nent
Tracking and Reporting	Universal Login Manager (ULM): Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device. uniFLOW Online Express: Combining with ULM you can gain further control and highlight expenditures per users/department and pinpoint where costs can be scaled down from a central cloud based location.
Remote Management Tools	iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and elerst, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management), remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.
Scanning Software	Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.
Optimisation Tools	Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers NetSpot Device Installer: Simple utility software that allows you to make network protocol settings for Canon devices connected to your network.
Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services
Document Publishing	iW Desktop: Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorisation.
Paper Supply Options	Concertes Faculture Link AD4
Name Paper Capacity	Cassette Feeding Unit-AP1 550 Sheets x 2 Cassettes (80 gsm)
Paper Size	A3, B4, A4, A4R, B5R, B5, A5R, A5, A6R Custom Size: 139.7 mm x 182.0 mm to 304.8 mm x 457.2 mm
Paper Weight	52 to 220 gsm
Power Source	From the Main Unit / Include in the Energy Concumption of main body
	E6E mm x 61E mm x 248 mm (Whon attached with the Main Linit)
Dimensions (W x D x H) Weight	565 mm x 615 mm x 248 mm (When attached with the Main Unit) Approx. 16 kg

Output Options Name	Inner 2Way Tray-J1
	Allows the separation of copies, prints and faxes. Adds a second internal output tray to give a combined output capacity of 350 sheets (upper tray 100 sheets/lower tray 250 sheets).
Copy Tray-J2	Provides a simple tray for basic output needs.
Name	Capacity: 100 srheets (A4, 80 gsm) Inner Finisher-K1
Number of Trays	2
Upper Tray: Capacity*	A4, A5, A5R, B5: 100 sheets, SRA3, A3, A4R, A6R, B4, B5R: 50 sheets
Lower Tray: Capacity*	A4, A5, A5R, B5: 500 sheets, SRA3, A3, A4R, B4, B5R 250 sheets,
	A6R: 30 Sheets *with 81.4 gsm paper
Paper Weight	52 to 300 gsm
Staple Position Staple Capacity	Corner, Double (with Lower Tray)
Staple Capacity	Corner staple and Double Staple: A4/B5: 50 sheets (52 to 90 gsm), A3, A4R, B4: 30 sheets (52 to 90 gsm) Staple-Free Staple: A3, A4, B4, B5: 5 sheets (52 to 64 gsm), 4 sheets (65 to 814 gsm), 3 sheets (815 to 105 gsm) Staple Once Brandt: 40 sheets (80 gsm)
Dimensions (W x D x H)	604 mm x 525 mm x 188 mm (unit size: when the extension tray is extended
Weight	Approx. 8 kg
Name	Staple Finisher-AA1 (External)
Number of Trays	2
Upper Tray Capacity*	A4, A5, A5R, A6R, B5: 250 sheets, SRA3, A3, A4R, B4, B5R: 125 sheet
Lower Tray Capacity*	A4, A5, A5R, B5: 3,000 sheets, SRA3, A3, A4R, B4, B5R: 1,500 sheets, A6R: 250 sheets with 81.4 gsm paper
Paper Weight	Top Tray: 52 to 256 gsm Lower Tray: 52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner staple and Double Staple: A4/B5: 50 sheets (52 to 90 gsm), A3/A4/R/B4: 30 sheets (52 to 90 gsm) Staple-Free Staple: A3/A4: 5 sheets (52 to 64 gsm), 4 sheets (65 to 81.4 gsm), 3 sheets (81.5 to 105 gsm) Staple On Demand: 50 sheets (90 gsm)
Power Source	From the Main Unit
Dimensions (W x D x H)	637 mm x 623 mm x 1,016 mm
Weight	(attached to the main unit, when the extension tray is extended) Approx. 30 kg
Name	Booklet Finisher-AA1 (External)
	(includes the Staple Finisher-AA1 basic staple specifications)
Number of Trays	2
Top Tray Capacity	A4, B5, A5, A5R 250 sheets, A3, B4, A4R, B5R, SRA3 125 sheets
Lower Tray Capacity	A4, B5, A5, A5R 3,000 sheets, A3, B4, A4R, B5R, SRA3 1,500 sheets
Paper Weight	Top Tray: 52 to 256 gsm Lower Tray: 52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner staple and Double Staple: A4/B5: 50 sheets (90 gsm), A3/B4/A4R: 30 sheets (90 gsm) Staple-Free Staple: A3/A4: 5 sheets (52 to 64 gsm), 4 sheets (65 to 81.4 gsm), 3 sheets (81.5 to 105 gsm) Staple On Demark: 50 sheets (90 gsm)
Booklet Stitch Paper Size	A3, A4R, B4, Custom Size (195.0 mm x 270 mm to 304.8 mm x 457.2 mm)
Booklet Stitch Staple Capacity	20 sheets (52 to 81.4 gsm) x 10 sets (including 1 cover sheet up to 256 gsm
Power Source	From the Main Unit
Dimensions (W x D x H)	637 x 623 x 1,016 mm
	(attached to the main unit, when the extension tray is extended)
Weight	Approx. 53 kg
Name	2/3 Hole Puncher Unit-A1, Two or Three Holes *Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, B4R, A4, A4R, A5, B5, B5R, Three holes: A3, B4R, A4, B5
Power Source	From the Main Unit
Name	2/4 Hole Puncher Unit-A1: Two or Four Holes *Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, B4R, A4, A4R, A5, B5, B5R, Four holes: A3, A4
Power Source	From the Main Unit
Hardware Accessories	
Card Readers	MICARD PLUS PROXIMITY CARD READER, IC Card Reader Box-C1/C2 , Copy Card Reader-F1, Copy Card Reader, Attachment-B5
Others	Utility Tray-B1, Platen Cover Type W, 3 Way Unit-D1
Security Options	
Document Security	Document Scan Lock Kit- B2, iR-ADV Security Kit-AC1 for IEEE 2600 Common Criteria Certification
Data Security	2.5inch/1TB HDD-P1, Removable HDD Kit-AK2
System and Controller Options	
Print Accessories	PCL International Font Set-A1 PS Printer Kit-BJ1
Send Options	Universal Send Digital User Signature Kit-C1 Universal Send Advanced Feature Set-H1 (Trace and Smooth PDF, Searchable PDF/XPS, Office Open XML)
Barcode Printing	(Trace and Smooth PDF, Searchable PDF/XPS, Office Open XML) Barcode Printing Kit-D1
System Accessories	Serial Interface Kit-K3, Copy Control Interface Kit-A1, Connection Kit-A1
	for Bluetooth LE, NFC Kit-C1
Fax Accessories	Super G3 Fax Board-AZ1, Super G3 2nd Line Fax Board-AZ1,
	Super G3 Fax Board-AZ1, Super G3 2nd Line Fax Board-AZ1, Remote Fax Kit-A1, IP Fax Expansion Kit-B1
Fax Accessories	

For information and services contact

Canon Australia Pty Ltd1800 444 199canon.com.auCanon New Zealand Ltd0800 222 666canon.co.nz





