

freedom
to focus

Canon

BUILT ON AWARD-WINNING SUCCESS

The imageRUNNER ADVANCE C5500i III Series platform brings you customisable workflows to help you increase productivity and track your progress.

imageRUNNER ADVANCE C5500i III Series

- Print up to 60 ppm in black & white and colour
- Scan up to 160/160 ipm
- Print up to SRA3
- 6,350-sheet paper capacity



MOBILITY

Organisational mobility allows for an innovative way of working, keeping users connected on the go

- Simple and easy mobile connectivity with in-built wifi
- Flexible mobile workflows enable users to intuitively print, scan and capture directly on their mobile with Canon PRINT Business
- Support for Apple AirPrint, Mopria and Google Cloud



SECURITY

Safeguard data and ensure sensitive information remains secure

- Control who has device access with user authentication systems
- Ensure data is secure with hard drive encryption
- IPsec, port filtering capabilities and SSL technology keeps information private and secure throughout your network



INTEGRATION

Seamlessly integrate into new and existing systems

- Leverage Canon's MEAP platform to optimise processes integrating with a range of powerful document, capture and output management solutions
- Collaborate with key line of business applications and external systems
- Supports integration with popular cloud services like Google Drive and Box*

* Requires uniFLOW Online Express or uniFLOW Online subscription



Save time and resources with increased workflow productivity

- Intuitive, user-friendly interface with a large 10.1 WSVGA touchscreen and smart phone similarities
- My ADVANCE functions allow users to create their own personalised experience, tailored to meet their unique needs
- Streamline digital workflows with improved scanning abilities such as single-pass document feeder and automatic blank page removal
- High quality output systems with V2 colour imaging technology and a range of finishing options including stapling, booklet, staple on-demand and eco staple



Manage costs with ease thanks to improved efficiencies

- Reduce wastage with Forced Job Hold at the device allowing users to preview, change print settings and sample print before releasing the full job
- Manage print by applying print policies and monitoring output
- Control print costs by restricting access not only to the device but to functions by user such as colour and 1-sided printing
- Reduce downtime and use of IT resources with remote support and fleet management



Achieve environmental goals by incorporating responsible design and efficient operations

- Motion Sensor and Sleep Recovery Triggers reduce energy consumption
- Sustainable design introduced with recycled materials and bio-based plastics
- Minimise waste with default print settings including two-sided, and black and white options
- ENERGY STAR and Blue Angel qualified with leading-class, Typical Electricity Consumption (TEC) rating

CONFIGURATION

Booklet Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 50 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers



Inner 2 Way Tray

- Separates copies, prints and faxes
- Adds a second internal output tray



Buffer Pass Unit

- Transports paper to external finisher



Inner Finisher

- 1-tray, 550 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 45 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers

Staple Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 50 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers



Utility Tray



Copy Tray



Paper Deck Unit

- Supports A4
- Media weight 52-256 gsm
- 2,700 sheets (80 gsm)



ColorPASS-GX500

- PS/APPE
- 4GB/1TB
- Fiery FS200 Pro



imagePASS-PS1

- PCL/PS
- 2GB/500GB
- Fiery FS200

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm™ or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI™ management information systems, Web-to-Print systems, and popular pre-press workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules C5550i and C5560i only



Cassette Feeding Unit

- Supports up to A3
- Media weight 52-256 gsm
- 2 x 550 sheets (80 gsm)



High Capacity Cassette Feeding Unit

- Supports A4
- Media weight 52-256 gsm
- 2,450 sheets (80 gsm)

imageRUNNER ADVANCE C5500i III SERIES SPECIFICATIONS



Main Unit	
Type	A3 Colour Laser Multifunctional
Core Function	Print, Copy, Scan, Send, Store and Optional Fax
Processor	Canon Dual Custom Processor (Shared)
Control Panel	25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel
Memory	Standard: 4GB RAM
Hard Disk Drive	Standard: 250GB Maximum: 1TB
Mirroring Hard Disk Drive	Optional: 250GB, 1TB
Interface Connection	Network: Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy Others: Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device) Optional: Serial Interface, Copy Control Interface
Paper Supply Capacity (A4, 80gsm)	Standard: 1,200 sheets 2 x 550-sheet cassettes, 100-sheet multi-purpose tray Maximum: 6,350 sheets (with High Capacity Cassette Feeding Unit-A1 & Paper Deck Unit-F1)
Paper Sources (80gsm)	Standard: Two 550-sheet Paper Cassettes 100-sheet Multi-purpose tray Optional: Dual 550-sheet Paper Cassettes (Cassette Feeding Unit-AM1), 2,450-sheet Paper deck (High Capacity Cassette Feeding Unit-A1), 2,700-sheet Paper deck (Paper Deck Unit-F1)
Paper Output Capacity (A4, 80gsm)	Standard: 250 sheets Maximum: 3,450 Sheets (with Staple Finisher-Y1 or Booklet Finisher-Y1 and Copy Tray-J2)
Finishing Capabilities	Standard: Collate, Group With Inner Finisher : Collate, Group, Offset, Staple, Hole Punch*1, Staple-Free Staple, Staple On Demand With External Finisher*2 : Collate, Group, Offset, Staple, Saddle Stitch*3, Hole Punch*4, Eco Staple, Staple On Demand *1 Requires Inner 2/3 Hole Puncher-B1 or Inner 2/4 Hole Puncher-B1 *2 Requires Buffer Pass-L1 *3 Requires Booklet Finisher-Y1 *4 Requires 2/3 Hole Puncher Unit-A1, 2/4 Hole Puncher Unit-A1 or 4 Hole Puncher Unit-A1
Supported Media Types	Upper Cassette 1: Thin, Plain, Thick, Colour, Recycled, Pre-punched, Transparency, Bond, Envelope, Letterhead Lower Cassette 2: Thin, Plain, Thick, Colour, Recycled, Pre-punched, Transparency, Tab*, Bond, Envelope, Letterhead * Requires Tab Feeding Attachment-F1 Multi-purpose tray: Thin, Plain, Thick, Colour, Recycled, Pre-punched, Transparency, Tracing*, Label, Tab, Bond, Coated, Envelope, Letterhead * Some types of tracing paper cannot be used. "
Supported Media Sizes	Cassette1: Standard size: A4, A5, A5R, A6R, B5, Envelope [No.10 (COM10), DL, ISO-C5] Custom Size : 98.0 x 148.0 mm to 297.0 x 215.9 mm Cassette 2 Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5] Custom size: 98.0 x 182 mm to 304.8 x 457.2 mm Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Envelopes [No. 10(COM 10), Monarch, ISO-C5, DL] Envelope Custom Size (98.0 x 98.4 mm to 320.0 x 457.2 mm) Custom Size : 98.0 x 139.7 mm to 320.0 x 457.2 mm Free Size: 98.0 x 139.7 mm to 320.0 x 457.2 mm
Supported Media Weights	Cassettes: 52 to 256 gsm Multi-purpose tray: 52 to 300 gsm Duplex: 52 to 220 gsm
Warm-up Time	From Power On: 10 seconds or less* *Time from device power-on, until copy ready (not print reservation). From Deep Sleep Mode: 10 Seconds or Less Quick Startup Mode: 4 Seconds or less * *Time from device power-on to when key operations can be performed on the touch panel display.
Dimensions (W x D x H)	620 mm x 742 mm x 950 mm
Installation Space (W x D)	Basic: 980 x 1,176 mm (with right cover open + cassette drawers open) Fully Configured: 1,866 x 1,176 mm (Booklet Finisher-Y1 with the extension tray extended + Paper Deck Unit-F1 + Cassette Drawers open)
Weight*	Approx. 142kg *Including toner

Print Specifications	
Printing Method	Colour laser
Print Speed* (ppm, BW and CL)	IR-ADV C5560i III: Up to 60 (A4, A5, A5R, A6R), Up to 32 (A3), Up to 36 (A4R) IR-ADV C5550i III: Up to 50 (A4, A5, A5R, A6R), Up to 27 (A3), Up to 30 (A4R) IR-ADV C5540i III: Up to 40 (A4, A5, A5R, A6R), Up to 22 (A3), Up to 24 (A4R) IR-ADV C5535i III: Up to 35 (A4, A5, A5R, A6R), Up to 18 (A3), Up to 23 (A4R)
(*simplex)	
Print Resolution (dpi)	1200 x 1200* *Laser Resolution
Page Description Languages	UFR II, PCL6 (Standard) Adobe PS 3 (Optional)
Double Sided Printing	Automatic (Standard)
Direct Print	Direct printing available from USB memory, Advanced box, Remote UI and Web Access (Only PDF print from websites is supported) Supported File Types: PDF, TIFF, JPEG, EPS, XPS
Printing from Mobile and Cloud	A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2 PS fonts: 136 Roman *1 Requires optional PCL International Font Set-A1 *2 Requires optional Barcode Printing Kit-D1
Print Features	Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold Printing
Operating System	UFR II: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.9 or later) PCL: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 PS: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.9 or later) PPD: MAC OS X (10.3.9 or later), Windows 7 / 8.1 / 10

Copy Specifications	
Copy Speed* (ppm, BW and CL) (*simplex)	IR-ADV C5560i III: Up to 60 (A4, A5, A5R, A6R), Up to 32 (A3), Up to 36 (A4R) IR-ADV C5550i III: Up to 50 (A4, A5, A5R, A6R), Up to 27 (A3), Up to 30 (A4R) IR-ADV C5540i III: Up to 40 (A4, A5, A5R, A6R), Up to 22 (A3), Up to 24 (A4R) IR-ADV C5535i III: Up to 35 (A4, A5, A5R, A6R), Up to 18 (A3), Up to 23 (A4R)
First-Copy-Out Time (A4, BW/CL)	IR-ADV C5560i III: Approx. 2.9/4.5 seconds or less IR-ADV C5550i III: Approx. 3.5/5.2 seconds or less IR-ADV C5540i III: Approx. 4.1/6.1 seconds or less IR-ADV C5535i III: Approx. 4.9/7.4 seconds or less
Copy Resolution (dpi)	600 x 600
Copy Density	Automatic or Manual (9 Levels)
Magnification	25% - 400% (1% Increments)
Presets Reductions	25%, 50%, 61%, 70%, 81%, 86%
Presets Enlargements	115%, 122%, 141%, 200%, 400%
Special Copy Features	Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original, Colour Balance, Adjust One-Touch Colour, Area Designation

Scan Specifications	
Type	Colour Platen and Single-pass Duplexing Automatic Document Feeder * [2-sided to 2-sided (Automatic)] * Detect Feeder Multi Sheet Feed is supported.
Document Feeder	150 Sheets
Paper Capacity (80gsm)	
Supported Media Sizes	Platen: max. scanning size: 297.0 x 431.8 mm Document Feeder media size: A3, B4, A4, A4R, B5, B5R, A5, A5R, B6R Custom size: 128 x 139.7 mm to 304.8 x 431.8 mm
Document Feeder Supported Media Weights	Single-sided scanning: 38 to 157 gsm (BW) Single-sided scanning: 64 to 157 gsm (CL) Double-sided scanning: 50 to 157 gsm (BW) Double-sided scanning: 64 to 157 gsm (CL)
Pull Scan Spec	Colour Network ScanGear2. For both Twain and WIA Supported OS: Windows 7/8.1/10 / Windows Server 2003/Server 2003 R2 Server 2008/ Server 2008 R2/Server 2012/Server 2012 R2
Scan Resolution (dpi)	100 x 100, 150 x 150, 200 x 100, 200 x 200, 200 x 400, 300 x 300, 400 x 400, 600 x 600
Platen Acceptable Originals	Platen: Sheet, Book, 3-Dimensional Objects (Height: Up to 50 mm, Weight: up to 2kg) Feeder size: A3, (ipm: A4, BW/CL), A4R, A5, A5R, B4, B5, B5R, B6
Scan Speed (ipm: A4, BW/CL)	1-sided Scanning: 80/80 (300dpi) , 80/60 (600 dpi) 2-sided Scanning : 160/160 (300dpi) , 150/80 (600 dpi)
Double Sided Scanning	2-sided to 2-sided (Automatic)
Scan Method	Send functionality available on all models Scan to USB Memory: Available on all models Scan to Mobile Devices and Cloud-based Services: A range of solutions is available to provide scanning to mobile devices or cloud-based services depending on your requirements. Please contact your sales representative for further information. TWAIN/WIA Pull scanning available on all models

Send Specifications	
Optional/Standard	Standard on all models
Destination	E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 FAX(Optional), IPFax(Optional)
Colour Mode	Automatic-Colour Select (Full Colour/Grayscale), Automatic-Colour Select (Full Colour/Black-and-White), Full colour, Grayscale, and Black-and-White
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send Resolution (dpi)	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150 , 100 x 100
Communication Protocol	File: FTP (TCP/IP), SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3)
File Format	Standard: TIFF, JPEG, PDF (Limited Colour, Compact, Apply policy, Optimise for Web, PDF A/1-b, Encrypted, Device Signature), XPS (Compact, Device Signature) Optional: PDF(Searchable, Trace&Smooth, User Signature), XPS (Searchable, User Signature), Office Open XML (PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages, Detect Feeder Multi Sheet Feed

Fax Specifications	
Maximum Number of Connection Lines	4
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution	400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi
Sending/Recording Size	A3, A4, A4R, A5*1, A5R*1, B4, B5*2, B5R*1 *1 Sent as A4 *2 Sent as B4
FAX Memory	Up to 30,000 pages
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes
Fax Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density (for Scanning), Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line (When sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

Store Specifications	
Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, 30,000 Maximum Pages Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows 7/8.1/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)
Advanced Box Available Disc Space	Approx. 16GB (Standard HDD) Approx. 480GB (with option 1TB HDD)
Advanced Box Features	Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support
Memory Media	Standard: USB Memory

Security Specifications

Security	Safeguard data and ensure sensitive information remains secure
	Control who has device access with user authentication systems Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers. Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering. Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices. Ensure data is secure with hard drive encryption
Authentication	Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in, uniFLOW Online Express Optional: uniFLOW, uniFLOW Online
Data	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated) Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)
Network	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP , S/MIME
Document	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan lock

Environmental Specifications

Operating Environment	Temperature: 10 to 30°C Humidity: 20 to 80 % RH (Relative Humidity)
Power Requirements	220-240V(±10 %), 50/60Hz (±2 Hz), 6Amp
Power Consumption	Maximum: 1,800 W Standby: Approx. 64.8 W *1 Sleep mode: Approx. 0.8 W *2 *1 Reference Value (measured one unit) *2 0.8W sleep mode is not available in all circumstances due to certain settings.

Consumables

Toner	NPG-71 TONER BK/C/M/Y, NPG-71L TONER C/M/Y
Toner Yield (Estimated @5% Coverage)	NPG-71 TONER BK 69,000 pages NPG-71 TONER C/M/Y 60,000 pages NPG-71L TONER C/M/Y 26,000 pages

Software and Printer Management

Tracking and Reporting	Universal Login Manager (ULM): Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device. uniFLOW Online Express: Combining with ULM you can gain further control and highlight expenditures per users/department and pinpoint where costs can be scaled down from a central cloud based location.
Remote Management Tools	IW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.
Scanning Software	IW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.
Optimisation Tools	Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers NetSpot Device Installer: Simple utility software that allows you to make network protocol settings for Canon devices connected to your network.
Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services
Document Publishing	IW Desktop: Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorisation.

Fiery Print Controller Specifications

Optional/Standard	Optional on all models
Name	imagePASS-P2 (Embedded)
Print Resolution (dpi)	1200 x 1200, 600 x 600
Standard Page Description Languages	Adobe PS3, PCL6
Memory	4GB (1 x 4GB)
Hard Disk Drive	500 GB SATA
Processor	Intel Pentium G4400 (3.3 GHz)
System	Fiery FS350
Fonts	PS: 138 Fonts PCL: 113 Fonts
Supported Operating Systems	Windows 7 32 and 64 bit / Windows 8.1 32 and 64 bit / Windows10 32 and 64 bit / Windows Server 2012 64bit only / Windows Server 2012 R2 64bit only / Windows Server 2016 R2 64bit only/ MAC OS (10.11, 10.12, 10.13, 10.14)
Interface	2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 2 (Rear x 2), USB2.0 x 4 (Rear x 4)
Network Protocols	TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNTp, 802.1X, DHCP, DNS, NTP)
Direct Print	PDF1.7, EPS, TIFF6, JDF1.4/JMF(OP)
VDP	FreeForm v1, v2.1
Fiery Print Controller Standard Features	Fiery Command WorkStation 6 / Paper Catalog / Fiery Spot-On / Fiery Remote Scan
Fiery Print Controller Options	Fiery Impose / Fiery Compose / Fiery Impose and Compose / Productivity Package Web Activate (Include Fiery JDF) / Fiery Hot Folders & Virtual Printers

HW Platform	E400
Base OS	Debian of Linux
Maximum Power Consumption	47W
Weight	Fiery unit only (with plate): 4.95 kg
Dimensions (W x D x H)	285 x 93 x 295 mm

Paper Supply Options

Name	Cassette Feeding Unit-AM1
Paper Capacity	550 Sheets x 2 Cassettes (80 gsm)
Paper Type	Thin, Plain, Thick, Colour, Recycled, Pre-punched, Transparency, Bond, Letterhead
Paper Size	A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Custom size: 98.0 x 182.0 mm to 304.8 x 457.2mm
Paper Weight	52 to 256 gsm
Power Source/Max. Power Consumption	From the Main Unit
Dimensions (W x D x H)	620 mm x 700 mm x 251 mm (When attached with the Main Unit)
Weight	Approx. 22.5 kg
Name	High Capacity Cassette Feeding Unit-A1
Paper Capacity	2,450 sheets (80 gsm)
Paper Type	Thin, Plain, Thick, Colour, Recycled, Pre-punched, Bond, Letterhead
Paper Size	A4
Paper Weight	52 to 256 gsm
Power Source/Max. Power Consumption	From the Main Unit
**Dimensions (W x D x H)	620 mm x 700 mm x 251 mm (When attached with the Main Unit)
Weight	Approx. 30 kg
Name	Paper Deck Unit-F1
Paper Capacity	2,700 sheets (80 gsm)
Paper Size	A4, B5
Paper Type	Thin, Plain, Thick, Colour, Recycled, Pre-punched, Bond, Letterhead
Paper Weight	52 to 256 gsm
Power Source	From the Main Unit
Dimensions (W x D x H)	344 x 630 x 440 mm (attached to the main unit)
Weight	Approx. 31 kg

Output Options

Copy Tray-J2	Provides a simple tray for basic output needs. Capacity: 100 sheets (A4, 80 gsm)
Name	Inner 2-Way Tray-J1
Number of Trays*	2
Total Output Capacity	Allows the separation of copies, prints and faxes. Adds a second internal output tray to give a combined output capacity of 350 sheets (upper tray 100 sheets/lower tray 250 sheets), (A4, 80 gsm)
Paper Size	Standard size: A3, B4, A4, A4R, B5, B5R, A5, A5R, SRA3, Envelope (No.10(COM10), Monarch, DL, ISO-C5), Envelope Custom Size (98.0 mm x 98.4 mm to 320 mm to 457.2 mm) Custom Size: 98.0 mm x 139.7 mm to 320 mm x 457.2 mm
*Dimensions (W x D x H)	427 mm x 407 mm x 76 mm (When attached with the Main Unit)
Weight	Approx. 0.6 kg
Name	Inner Finisher-H1
Number of Trays	2
Upper Tray Capacity*	SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R: 45 sheets
Lower Tray Capacity*	A4, A5, A5R, B5: 500 sheets, SRA3, A3, A4R, B4, B5R : 250 sheets, A6R: 30 sheets * with 81.4 gsm paper
Paper Weight	52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner and Double Stapling: A4, B5: 50 sheets (52 to 90 gsm) A3, A4R, B4: 30 sheets (52 to 90 gsm) Staple-Free Staple: A3, A4, B4, B5: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm) 3 sheets (81.5 to 105 gsm) Staple On Demand: 40 sheets (80 gsm)
Dimensions (W x D x H)	466 x 525 x 225 mm (unit size) [743 x 742 x 225 mm (when the extension tray is extended, attached to the main unit)]
Weight	Approx. 8.6 kg
Name	4 Hole Puncher Unit-A1 (Requires either the Staple Finisher-Y1 or Booklet Finisher-Y1) Four Holes

Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Four holes A3, A4, A4R, A5, B4, B5, B5R
Power Source	From the Main Unit
Name	Staple Finisher-Y1(External) (Requires Buffer Pass Unit-L1)
Number of Trays	2
Upper Tray Capacity	A4, A5, A5R, A6R, B5: 250 sheets, SRA3, A3, A4R, B4, B5R: 125 sheets
Lower Tray Capacity	A4, A5, A5R, B5: 3,000 sheets, SRA3, A3, A4R, B4, B5R: 1,500 sheets, A6R: 250 sheets * with 81.4 gsm paper
Paper Weight	Upper Tray 52 to 256 gsm, Lower Tray 52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner and Double Stapling: A4, B5: 50 sheets (52 to 90 gsm) A3, A4R, B4: 30 sheets (52 to 90 gsm) Staple-Free Staple: A3, A4: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm) 3 sheets (81.5 to 105 gsm) Staple On Demand: 50 sheets (90 gsm)
Dimensions (W x D x H)	637 mm x 623 mm x 1,142 mm (When the extension tray is extended)
Weight	Approx. 31 kg
Name	Booklet Finisher-Y1 (External) (Requires Buffer Pass Unit-L1) (Includes the above STAPLE FINISHER-Y1 basic staple specifications.)
Staple Capacity	Corner and Double Stapling: A4/B5: 50 sheets (52 to 90 gsm) A3/B4/A4R: 30 sheets (52 to 90 gsm) Staple: A3/A4: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm) 3 sheets (81.5 to 105 gsm) Staple On Demand: 50 sheets (90 gsm)

Saddle Stitch size	A3, A4R, B4, Custom Size (195.0 x 270.0 mm to 304.8 x 457.2 mm)
Saddle Stitch Staple Capacity	20 sheets x 10 sets (81 gsm) (Including 1 cover sheet up to 256 gsm)
Non Staple Folded Bunch Capacity	up to 3 sheets (52 to 105 gsm)
Dimensions (W x D x H)	637 x 623 x 1,142 mm (when the extension tray is extended)
Weight	Approx. 57 kg
Inner 2/3 Hole Puncher-B1	(Requires the Inner Finisher-H1)
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes A3, A4, A4R, A5, B4, B5, B5R, Three holes A3, A4, B4, B5
Power Source	From the Main Unit
Inner 2/4 Hole Puncher-B1	(Requires the Inner Finisher-H1) Two or Three Holes
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes :A3, A4, A4R, A5, B4, B5, B5R, Four holes: A3, A4
Power Source	From the Main Unit
2/3 Hole Puncher Unit-A1	(Requires either the Staple Finisher-Y1 or Booklet Finisher-Y1) Two or Three Holes
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, A4, A4R, A5, B4, B5, B5R, Three holes A3, A4, B4, B5
Power Source	From the Main Unit
2/4 Hole Puncher Unit-A1	Two or Four Holes (Requires either the Staple Finisher-Y1 or Booklet Finisher-Y1)
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, A4, A4R, A5, B4, B5, B5R, Four holes: A3, A4
Power Source	From the Main Unit
Hardware Accessories	
Tab Feeding Attachment-F1, Utility Tray-B1	
Card Readers	MiCARD PLUS PROXIMITY CARD READER, IC Card Reader Box-C1/C2
Others	Tab Feeding Attachment-F1, Utility Tray-B1
Security Options	
Document Security	Document Scan Lock Kit- B2, iR-ADV Security Kit-AE1 for IEEE 2600 Common Criteria Certification
Data Security	HDD Mirroring Kit-J1, 2.5 inch/250GB HDD-N1, 2.5 inch/1TB HDD-P1, Removable HDD KIT-AL1
System and Controller Options	
Print Accessories	PCL International Font Set-A1 , PS Printer Kit-BE1
Send Options	Universal Send Advanced Feature Set-H1 (Trace & Smooth PDF, Serchable PDF/XPS, OfficeOpen XML), Universal Send Digital User Signature Kit-C1
Barcode Printing	Barcode Printing Kit-D1
EFI-Fiery Based Controller	imagePASS-P2
EFI-Fiery Based Controller Options	Productivity Package Web Activate Hot Folders Licences (Hot Folders & Virtual Printers) Fiery Impose Fiery Compose Fiery Impose and Compose
System Accessories	Copy Control Interface Kit-A1 Serial Interface Kit-K3 Connection Kit-A1 for Bluetooth LE NFC Kit-C1
FAX Accessories	Super G3 Fax Board-AS1, Super G3 2ND Line Fax Board-AS1, Super G3 3rd/4th Line Fax Board-AS1, Remote Fax Kit-A1 IP FAX Expansion Kit-B1
Other Options	
Accessibility Accessories	ADF Access Handle-A1, Voice Guidance Kit-G1, Voice Operation Kit-D1
Consumables	Stamp Ink Cartridge-C1, Staple-P1, Staple Cartridge-Y1 Stamp Unit-B1

For information and services contact

Canon Australia Pty Ltd 1800 444 199 **canon.com.au**
Canon New Zealand Ltd 0800 222 666 **canon.co.nz**

POWERED BY  **uniFLOW**
 online
 express

freedom
to focus

Canon